

DRUM CODE: \_\_\_\_\_

CUSTOMER: \_\_\_\_\_ GBC ORDER NO.: \_\_\_\_\_ DATE: \_\_\_\_\_

**GREIF BROS. CORPORATION  
CLOSURE NOTIFICATION FORM**

Pursuant to the requirements of the Department of Transportation in CFR 49 Part 178.2(c)(1), this is your notification of the closing method used for the containers sold to you on the attached delivery ticket or bill of lading. This method of closure should be used to ensure that your containers have been closed in the same manner as when they were initially tested. If there is any question regarding proper closing methods, contact your local Greif salesperson or manufacturing facility. "Effective until further notice".

To Close:

- 1) Place cover on drum.
- 2) Snap the closing ring over the cover and top lip of the drum. Make sure that the writing on the closing lever is right side up. Also, make sure the bottom edge of the closing ring engages under the top lip of the drum.
- 3) Pull the locking lever closed. At the same time, tap along the entire outside edge of the closing ring, beginning directly opposite the closing lever, with a mallet until the lever is fully closed against the edge of the ring.
- 4) Snap the latch into the lever until it locks, then apply a sealing wire or other sealing device through the holes on the latch lever.
- 5) Drums closed in this manner have met the UN performance test requirements as specified in the container markings.

REV-JG-12/14/00

#### DISCLAIMERS

Tests were conducted using water for liquid containers, sand and sawdust for solid containers, or water and anti-freeze mixture for plastic drums used to contain liquids. Your product may adversely affect container materials, bung threads, or closing devices. Product compatibility with the container is a shipper's responsibility.

These instructions for container closure are based upon the closure methods used to enable these containers to pass the United Nations test requirements as outlined by the UN marking on the package.

These closure recommendations do not take into account any hazards present in your facility, or the handling, filling, or shipping of your product. The use of sparkless tools and proper safety equipment is recommended. Consult your supervisor for your special safety precautions.

Any containers used for packing of hazardous materials should be inspected prior to filling and shipment. Containers with obvious damage or deterioration should not be filled or shipped.